

Capacitor, Tantalum, SMD, Polymer, Molded, Low ESR, Non-Combustible, 330 uF, 7343, +/-20% Tol, 16 V (105C)



General Information	
Supplier:	KEMET
Brand:	Kemet
Application:	General Purpose/Low ESR
Sub Application:	(NonCombustibleCathode)
Part Type Description:	SMD, Polymer, Molded, Low ESR, Non-Combustible
Construction:	Standard Chip-Polymer
Body Type:	Molded Chip
Termination:	Tin
Footprint:	7343
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	7.30	+/-0.3
W	4.30	+/-0.3
H	4.00	+/-0.3
F	2.40	+/-0.1
S	1.30	+/-0.3
B	0.50	+/-0.15
X	0.10	+/-0.1
P	1.70	REF
R	1.00	REF
T	0.13	REF
A	3.80	MIN
G	3.50	REF
E	3.50	REF

Specifications	
Capacitance:	330 uF
Tolerance:	+/-20%
Voltage:	16 V (105C)
Voltage:	10.72 V (125C)
Temperature Range:	-55/+125C
Current/Ripple Current:	3100 mA (25C)
Current/Ripple Current:	2790 mA (85C)
Current/Ripple Current:	1240 mA (125C)
Resistance/ESR:	25 mOhms (100kHz)
Failure Rate:	NA
Leakage Current:	528 uA
Dissipation Factor:	10%

Packaging Specifications	
Package Kind:	T&R
Package Size:	7in
Package Quantity:	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.